

COMPLETE
FITNESS
SOLUTIONS



EXPERIENCE SERIES™
830 Line

PRECOR®



Experience Series™ 830 Line

Introducing the **Experience Series™ 830 Line**, where tried and true technology and performance gets a fresh look and feel – along with a technology update that's fit for today.

Right from the start, you'll see that the form and function of the 830 Line console complements the 880 Line console, right down to the same easy-to-use motion controls. From there, the 830 Line console uses an LED-based display that focuses on the essential fitness stats and displays that keep members moving.

And, just as with all Experience Series™ cardio, the 830 Line features the same smooth, flowing, and precise cardio equipment from Precor – now refined for 2011.

P30 Console Specifications

| | |
|-------------------------------|---|
| Display Type | Large LED Display |
| Machine Controls | Motion Controls |
| Numeric Key Pad | Standard |
| Units Selection | Metric and U.S. Standard |
| Languages | English, French, Dutch, German, Italian, Russian, Spanish |
| Reading Rack | Standard |
| Personal Viewing System (PVS) | Optional - 15" PVS |
| Entertainment Cap | Optional - 800 / 900 MHz |



Adaptive Motion Trainer® **AMT® 835**

- User-defined motion
- Total body exercise
- Stride length between 0 and 27 inches (69 cm)



Elliptical Fitness Crosstrainer™ **EFX® 835**

- CrossRamp® technology: adjustable ramp between 13 and 40°
- Total body workout
- Moving upper body handlebars



Elliptical Fitness Crosstrainer™ **EFX® 833**

- CrossRamp® technology: adjustable ramp between 13 and 40°
- Fixed upper body handlebars



Treadmill **TRM 833**

- Incline range: 0% to 15% incline
- Ground Effects® Impact Control System
- Integrated Footplant Technology™
- 0.5-16 mph / 1-25.5 km/h
- 4.0 hp AC motor with IFT
- Auto stop™



Upright Bike **UBK 835**

- Over-molded handlebars
- Ergonomically designed saddle
- Dual-sided pedals with integrated straps
- Simple single-handed seat adjustment



Recumbent Bike **RBK 835**

- Step-through design
- Ventilated, suspension-mounted air flex seat back
- Dual-sided pedals with integrated straps
- Simple single-handed seat adjustment



Climber **CLM 835**

- Smooth feel and quiet movement
- Self-powered generator resistance system
- Belt drive system

| | AMT® 835 | EFX® 835 | EFX® 833 | TRM 833 | UBK 835 | RBK 835 | CLM 835 |
|---|-------------------|------------------|------------------|----------------------------|-----------------|-----------------|------------------|
| Console Features | | | | | | | |
| Stride Dial™ | ■ | - | - | - | - | - | - |
| Muscle Monitor™ | - | ■ | ■ | - | - | - | - |
| Numeric Keypad | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| QuickStart™ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Motion Controls | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Heart Rate Monitoring | | | | | | | |
| Touch | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Telemetry (Chest Strap Required) | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Equipment Features | | | | | | | |
| Adjustable Stride Length | 0-27 in / 0-69 cm | - | - | - | - | - | - |
| CrossRamp® Technology | - | 13 - 40° | 13 - 40° | - | - | - | - |
| Ground Effects® Technology | - | - | - | ■ | - | - | - |
| Integrated Footplant Technology™ | - | - | - | ■ | - | - | - |
| Auto Stop™ | - | - | - | ■ | - | - | - |
| Incline | - | - | - | 0% - 15% (0.5% increments) | - | - | - |
| Resistance Levels | 20 | 20 | 20 | - | 25 | 25 | 31 |
| Step-up Height | 5.5 in / 14 cm | 8 in / 20 cm | 8 in / 20 cm | 11.6 in / 29.5 cm | - | - | - |
| Speed | - | - | - | 0.5-16 mph / 1-25.5 km/h | - | - | - |
| Integrated Transport Wheels | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Workouts | | | | | | | |
| Total Workouts* | 4 | 15 | 10 | 25 | 12 | 12 | 14 |
| Electronic Readouts | | | | | | | |
| Total Readouts* | 21 | 21 | 21 | 21 | 18 | 18 | 21 |
| Network Capabilities | | | | | | | |
| CSAFE-enabled | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Entertainment Options | | | | | | | |
| Personal Viewing System (PVS) | O | O | O | O | O | O | O |
| Entertainment Cap | O | O | O | O | O | O | O |
| Language selection | | | | | | | |
| English, French, Dutch, German, Italian, Russian, Spanish | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Units Selection | | | | | | | |
| Metric | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Standard | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Product Dimensions | | | | | | | |
| Inches (LxWxH) | 74 x 28 x 69 | 80 x 32 x 68 | 80 x 32 x 68 | 88 x 35 x 64 | 48 x 21 x 62 | 67 x 23 x 50 | 47 x 32 x 69 |
| Centimeters (LxWxH) | 188 x 71 x 176 | 203 x 81 x 173 | 203 x 81 x 173 | 224 x 89 x 163 | 122 x 53 x 157 | 170 x 58 x 127 | 119 x 81 x 175 |
| Product Height with PVS | 82 in / 208 cm | 84 in / 213 cm | 84 in / 213 cm | 80 in / 203 cm | 72 in / 183 cm | 63 in / 160 cm | 85 in / 208 cm |
| Product Weight | 445 lbs / 202 kg | 338 lbs / 153 kg | 338 lbs / 153 kg | 456 lbs / 207 kg | 160 lbs / 73 kg | 210 lbs / 95 kg | 250 lbs / 113 kg |
| Power | | | | | | | |
| Self-Powered | ■ | ■ | ■ | Powered | ■ | ■ | ■ |
| Accessories | | | | | | | |
| Accessories Holder | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Reading Rack | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Cable Management | O | O | O | O | O | O | O |
| Regulatory Approvals | | | | | | | |
| FCC, ETL, CE, EN957 | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Warranty | | | | | | | |
| Frame | 7 years | 7 years | 7 years | 7 years | 7 years | 7 years | 7 years |
| Parts (Mechanical & Electronic) | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years | 2 years |
| Wear Items | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year |
| Labor | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year | 1 year |

KEY: ■ Standard O Optional - Not available

* Visit www.precor.com for the most recent information on all our products



Precor Incorporated, 20031 142nd Avenue NE, P.O. Box 7202, Woodinville, WA 98072-4002,
Tel: +1 (0) 425-486-9292, Fax: +1 (0) 425-486-3856, E-mail: commsls@precor.com, www.precor.com

© Precor Incorporated 2011. Precor reserves the right to make any changes without prior notice.